



US 20170174337A1

(19) **United States**(12) **Patent Application Publication**
Roberts et al.(10) **Pub. No.: US 2017/0174337 A1**(43) **Pub. Date: Jun. 22, 2017**(54) **REDUNDANT AIRCRAFT PROPULSION
SYSTEM USING MULTIPLE MOTORS PER
DRIVE SHAFT****B64C 39/02** (2006.01)**B64C 27/46** (2006.01)(52) **U.S. Cl.**CPC **B64C 27/14** (2013.01); **B64C 27/46**
(2013.01); **B64C 11/48** (2013.01); **B64C**
39/024 (2013.01); **B64C 2201/024** (2013.01);
B64C 2201/108 (2013.01)(71) Applicant: **Amazon Technologies, Inc.**, Seattle,
WA (US)(72) Inventors: **Nicholas Hampel Roberts**, Seattle, WA
(US); **Dominic Timothy Shiosaki**,
Seattle, WA (US); **Ricky Dean Welsh**,
Bellevue, WA (US)(21) Appl. No.: **14/973,618**(22) Filed: **Dec. 17, 2015****Publication Classification**(51) **Int. Cl.****B64C 27/14** (2006.01)**B64C 11/48** (2006.01)**ABSTRACT**

Multiple motors may drive (rotate) a single shaft coupled to a propeller. The motors may be selected such that a first motor is capable of rotating the drive shaft in an event of a failure of a second motor coupled to the drive shaft. A one-way clutch bearing, or similar device, may interface between a motor and the drive shaft to enable free rotation of the drive shaft in an event of the motor becoming inoperable, such as the motor freezing or locking in a position due to failure caused by overheating or caused by other conditions or events. Use of the second motor may secure a position of the drive shaft which may support the propeller in radial eccentric loading.

